

Windows Custom-Application Terminal

SIMPLE POWERFUL FLEXIBLE

FLEXIBLE WINDOWS CUSTOM-APPLICATION TERMINAL (LOCAL APPLICATION SUPPORT AND RICH EMBEDDED BROWSER) WITH LEGACY PORTS AND EXPANDABLE STORAGE OPTIONS.

Key Features	Key Benefits
Supports embedding of customer-selected local Windows 32-bit applications	Delivers the flexibility, performance, and power of the Windows operating system
Microsoft Windows XP Embedded	Latest OS environment, vast peripheral and device driver support ability to embed local apps
Optional hardware upgrades	For customers who need local disk drive, modem, or expanded connectivity in a thin client
Microsoft MediaPlayer, on board AGP video and 3D sound optional	Access true multimedia applications at the desktop
Local Windows XP desktop interface, also displays Windows XP desktops and applications via multiuser Windows NT and Windows 2000 servers	Failure-proof solution (Key application runs either on the server or locally)
Supports RDP 5 and ICA 6 protocols	Flexibility to choose optimal protocol
Connects to any VESA standard monitor	Flexibility to use almost any monitor
10/100BaseT Fast Ethernet with WakeOnLan, one serial, one parallel, and two USB ports, PCI/ISA slot	Fast LAN/WAN connectivity, robust peripheral support, optional dial-up capabilities
Remote management and configuration through Wyse Rapport administrative software	"Visit-free" management, upgrades, and configuration from administrator's console
Built-in Microsoft Internet Explorer 6.0	Direct web access, local JVM, optional IE plug-ins

Three-year Buyer's Protection Plan

Assurance of reliability, availability, and performance, from the industry leader



Wyse® Winterm™ desktops are a better way to deliver Windows® applications to users throughout your enterprise – especially task oriented and general office workers. Our broad range of thin-client devices provide security, manageability, affordability, and reliability. They offer greater ease of deployment, administration, and use than any other desktop option.

The Winterm 9440XL, based on the Microsoft® Windows XP Embedded operating system, is the most flexible and expandable Wyse terminal to allow the embedding of local 32-bit Windows applications.

Vital Windows applications which cannot be server-based can be embedded on the model 9440XL, and with on board AGP video and 3D sound, multimedia applications can be accessed locally and experienced fully. Plus, with Internet Explorer 6.0, there is full local Internet and intranet access with plug-in support.

The Winterm 9440XL utilizes the Windows XP desktop interface, and has an unmatched array of connectivity and communications features. Its slim, modular design allows for use with most existing monitors.

The Winterm 9440XL is available in custom configurations with many unique peripheral options, including internal hard drive, CD-ROM drive, or floppy drive, plus a modem.

The Winterm 9440XL comes bundled with Wyse Rapport™, the enterprise client management tool that leverages the value of your IT infrastructure for maximum ROI.



Specifications

Windows Custom-Application Terminal

- Based on Windows XP Embedded operating system
- Integrated Microsoft RDP and Citrix ICA protocols and terminal personalities standard
- Modular design
- 144MB FLASH DOC
- 128MB DRAM (expandable to 256MB)

Display Support ²

- VESA monitor support, with DDC for automatic setting of resolution and refresh rate
- Colors: up to 24 bit
- Video: selectable, up to 1600x1200
- Flicker-free, 85 Hz maximum refresh rate (1600x1200 max refresh rate is 60Hz at 16-bit)

Audio ²

- Output: 1/8-inch mini, full 16-bit stereo, 48 KHz sample rate
- Input: 1/8-inch 8-bit mini microphone

Input/Output/Peripheral Support

- Keyboard: enhanced PS/2 with Windows keys (104 keys) included ³; low profile design with two-position tilt; detachable 5-foot (1.5-meter) cable
- Mouse: PS/2 mouse included
- Local and/or network printers
- VGA-type video output (DB-15)
- Two USB ports

Networking

- TCP/IP with DNS and DHCP
- 10/100BaseT Fast Ethernet, twisted pair (RJ-45)

Expandability

- Available factory-installed hardware options include 6GB hard drive, floppy disk drive, CD-ROM, 56K modem, PCMCIA adapter, multiple serial ports, Token Ring (specify at time of order)



Communications

- One serial port: 16C550 (fifo) compatible, up to 115.2 Kbaud
- One parallel port: bi-directional Centronics-compatible, DB-25
- Two USB ports

Firmware Features

- Microsoft Internet Explorer 6.0 resident: HTML, JavaScript, XML, Active X, JVM, Media Player 6.4, Citrix NFuse

- RDP 5 resident
- ICA 6, Program Neighborhood resident
- Pericom TeemNT 1.6 terminal emulation suite including: Wyse WY-60, WY-50, WY-50+; IBM TN3270e, TN5250, 3151; DEC VT420; ADDS A2; Hazeltine 1500; and SCO Console

Server OS Compatibility/Support

- Microsoft Windows 2000
- Microsoft Windows NT Server 4.0, Terminal Server Edition
- Citrix WinFrame®
- Citrix MetaFrame®

Management

- Send messages
- Remotely shadow desktop
- Complete image upgrade
- Wake terminal remotely (Wake on LAN)
- Terminal configuration (IP information, name, etc.)
- Reporting
- Remote management, configuration, and upgrades through Wyse client management software (included)

Set-Up and Configuration

User interface

- Local boot
- Keyboard language support: French, German, Italian, U.K. English, U.S. English standard, others optional

Configuration

- Remote screen shadowing of entire desktop (VNC)
- PXE (standard image updating mechanism)
- Remote management, configuration, and upgrades through Wyse Rapport management software (Rapport Agent v5.0 included)

Physical Characteristics (H x W x D)

- 9.5 x 1.9 x 8.6 in.
- 24 x 5.0 x 22 cm.

Environmental

Temperature range

- Powered on: 32° to 104°F (0° to 40° C)
- Powered off: -14° to 140°F (-10° to 60° C)

- Convection or fan cooling

Humidity

- 20% to 80% noncondensing
- Operating altitude range
- 0 to 10,000 feet (0 to 3,050 meters)

Power

- Worldwide auto-sensing 100-240 VAC, 47-63 Hz

Regulatory compliance

RF interference

- FCC Class B
- CE mark
- C-Tick

Warranty

- Three-year Buyer's Protection Plan (one-year limited hardware warranty, with service extended to three years free with registration in the first 90 days)

WYSE
| | | |

Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Wyse Sales:
800 GET WYSE
(800 438 9973)

International Sales:
Australia 61 2 9319 3388
France 33 1 39 44 63 85
Germany 49 89 460099 26
Taiwan 886 3 577 9261
UK 44 118 982 8335
United States 408 473 1200

Or send email to:
sales@wyse.com

Wyse Customer Service Center:
800 800 WYSE
(800 800 9973)

Visit our websites at:
<http://www.wyse.com.au>
<http://www.wyse.fr>
<http://www.wyse.de>
<http://www.wyse.com.tw>
<http://www.wyse.co.uk>
<http://www.wyse.com>

¹Applications are embedded by Wyse Technology or certified Authorized Winterm Partners. ²Monitor, speakers and microphone not included. ³Keyboard not included with international models.