

Windows-Based Terminal with CE.NET



SIMPLE POWERFUL FLEXIBLE

POWERFUL, SLEEK, WINDOWS-BASED TERMINAL (EMBEDDED INTERNET EXPLORER BROWSER) WITH LEGACY AND USB PORTS.

Key Features	Key Benefits
10/100Base-T Fast Ethernet, two serial, one parallel, and three USB ports	Fast LAN/WAN connectivity, robust peripheral support, dial-up capabilities
Optional windowing	Administrators can use a PC-like desktop with a task bar or the standard Simplified Connection Manager GUI to best meet the users' needs
Displays Windows desktops and applications from multiuser Windows NT, Windows 2000, and Microsoft Server 2003	Delivers the flexibility, power, and performance of Windows, without the overhead cost of PC service and support
Built-in Microsoft Internet Explorer	Local IE browser provides access to web-based applications and supports Citrix NFuse
Microsoft Windows CE .NET operating system	Industry-standard operating system
Wi-Fi [®] 802.11b USB LAN option	Simple wireless LAN connectivity
Supports RDP and ICA protocols	Flexibility to choose optimal protocol
Over 15 resident terminal emulations	Single desktop access to UNIX/host systems, Windows NT and Windows 2000
Connects to any VESA standard monitor	Flexibility to use almost any monitor
Convection cooled; no moving parts	Quiet, durable, low operating cost, low service, maintenance
Three-year Buyer's Protection Plan	Assurance of reliability, availability, and performance, from the industry leader

The Wyse[®] Winterm[™] 3360SE is the perfect solution for task work and light-duty office work. Workers in healthcare, manufacturing, and education environments find Wyse Winterm thin clients manageable and reliable. IT managers find the 3360SE to be secure and affordable.

Because the Winterm 3360SE includes Windows CE.NET, it provides enhanced support wireless connectivity, greater security and manageability. As a member of the powerful class of Winterm desktops, the model 3360SE offers a built-in Microsoft Internet Explorer 6.0 browser for easy intranet browsing and access to web applications. With built-in terminal emulation, it is an ideal transitional product for green-screen environments.

The attractive small chassis has legacy I/O ports, yet fits unobtrusively on the desktop or can be easily mounted on the wall or under a desk. Plus, as with all Winterm thin clients, the Winterm 3360SE comes bundled with Wyse[™] Rapport[®], the enterprise client management tool that leverages the value of your IT infrastructure for maximum ROI.



7595 Jenther Drive, Mentor, OH 44060
440.953.1119 • 800.457.8499
FAX 440.953.8341



Specifications

Windows-Based Terminal

- Based on Windows CE .NET operating system
- Integrated Microsoft RDP and Citrix ICA protocols and terminal personalities standard
- Available in 32MB Flash/64MB RAM

Display Support

- VESA monitor support, with DDC for automatic setting of resolution and refresh rate
- Colors: 16, or 256 or 65,536
- Video: selectable, up to 1280x1024 at 75 Hz at 8-bit color
- Flicker-free, 85 Hz noninterlaced refresh rate up to 1024x768 at 16 bit color

Audio^{1,2}

- Output: 1/8-inch mini, full 16-bit stereo, 48 KHz sample rate

Input/Output/Peripheral Support

- Two serial ports: 16C550 (fifo) compatible, up to 115.2 Kbaud
- One parallel port: bi-directional Centronics-compatible, DB-25
- One USB port
- One PCMCIA Slot
- Keyboard: enhanced PS/2 with Windows keys (104 keys) included³; low profile design with two-position tilt; detachable 5-foot (1.5-meter) cable
- Mouse: PS/2 wheel mouse included
- Local and/or network printers on ICA (virtual port redirection ready)
- VGA-type video output (DB-15)

Networking

- TCP/IP with DNS and DHCP
- 10/100Base-T Fast Ethernet, twisted pair (RJ-45)
- Point-to-Point Protocol (PPP)
- Multiple master browser support on ICA
- Supports Citrix load balancing on ICA
- SNMP support allows configuration of terminal settings, reporting of terminal configuration and attached devices, traps
- DHCP support for automatic firmware upgrades and unit configuration
- Microsoft VPN add-on standard

Communication Protocols/

Terminal Emulations Supported

- Microsoft RDP resident
- Citrix ICA resident
- Wyse WY-60, WY-50, WY-50+; IBM TN3270e, TN5250, 3151; DEC



VT420; ADDS A2; Hazeltine 1500; and SCO Console resident

Available Winterm Accessories and Add-ons

Visit www.wyse.com

- USB to serial converter cable
- USB to parallel converter cable
- USB Wi-Fi® 802.11b
- Mass storage devices
- Media Player
- Wyse Remote Shadow (VNC)
- JetCet
- ThinPrint®
- Wyse Local Smart Card
- Mounting bracket

Partner Solutions

- ActivCard smart card
- Identix BioTouch USB 200 Fingerprint Reader
- New Moon Canaveral iQ from Tarantella support
- Tarantella Enterprise 3 support

Server OS Compatibility/Support

- Microsoft Windows 2003 Server
- Microsoft Windows 2000
- Microsoft Windows NT Server 4.0, Terminal Server Edition
- Citrix MetaFrame
- Citrix WinFrame

Set-Up and Configuration

User Interface

- Local boot
- Start-up wizard for simple set-up
- Keyboard language support: Arabic (101), Arabic (102), Arabic (102) AZERTY, Belgian Dutch, Belgian French, Brazilian (ABNT), Canadian French, Canadian (Legacy), Canadian Multi Standard, Chinese (Simplified) - US Keyboard, Chinese (Traditional) - US Keyboard, Coatian, Czech, Danish, Dutch, English (UK), English (US), Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Italian (142), Japanese, Korean, Latin American, Norwegian, Polish (214), Polish (Programmers), Portuguese, Romanian, Russian, Slovak, Slovenian, Spanish, Spanish Variation, Swedish, Swiss French, Swiss German, Turkish F, Turkish Q, US International

Configuration and Management

- Optional windowing
- Configurable automatic login
- Individual scripting
- Remote management, configuration, and upgrades through Wyse client

management software Wyse Rapport (Workgroup edition included)

Physical Characteristics

- Height: 8.9 inches (226mm)
- Width: 2.4 inches (60mm)
- Depth: 6.9 inches (174mm)
- Shipping weight: 12.5lbs (5.5kg)
- Optional mounting bracket for installation beneath desk or on wall

Environmental

Temperature range

- Powered on: 32° to 104°F (0° to 40°C)
- Powered off: -14° to 140°F (-10° to 60°C)
- Convection cooling, fanless design

Humidity

- 20% to 80% noncondensing

Operating altitude range

- 0 to 10,000 feet (0 to 3,050 meters)

Power

- Worldwide auto-sensing 90-264 VAC, 47-63 Hz
- Wake-on-LAN ready

Regulatory Compliance

Ergonomics

- German ZH1/618
- EN29241-3 approved
- EPA Energy Star

Safety

- UL 1950, CSA 950
- TÜV-GS approved
- EN 60950 approved

RF interference

- FCC Class B
- CE mark
- EN55022B approved
- VCCI

Warranty

- Three-year Buyer's Protection Plan (one-year hardware warranty, with service extended to three years free with registration in the first 90 days)



7595 Jenther Drive, Mentor, OH 44060
440.953.1119 • 800.457.8499
FAX 440.953.8341



Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

¹Monitor or speakers and microphone not included. ²Requires support by server OS and protocol. ³Keyboard not included with international models.